



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : C09K 3/18, 3/00	A1	(11) International Publication Number: WO 99/16846 (43) International Publication Date: 8 April 1999 (08.04.99)
(21) International Application Number: PCT/US98/20300 (22) International Filing Date: 29 September 1998 (29.09.98) (30) Priority Data: 08/940,936 30 September 1997 (30.09.97) US 09/161,865 28 September 1998 (28.09.98) US (71)(72) Applicant and Inventor: SAPIENZA, Richard [US/US]; I Miller Avenue, Shoreham, NY 11786 (US). (74) Agent: CLEMENT, Alan, B.; Hedman, Gibson & Costigan, P.C., 1185 Avenue of the Americas, New York, NY 10036 (US).		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG). Published <i>With international search report.</i>
(54) Title: ENVIRONMENTALLY BENIGN ANTI-ICING OR DEICING FLUIDS (57) Abstract The present invention provides deicing compositions which are environmentally benign, a process for producing the composition from certain waste process streams, and methods of deicing and/or anti-icing.		

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakhstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

ENVIRONMENTALLY BENIGN ANTI-ICING OR DEICING FLUIDS

The present application is a continuation-in-part of Serial No. 08/940,936, filed September 30, 1997, now allowed.

5 The present invention relates to a deicing fluid composition. More particularly the present invention relates to a deicing fluid composition which is environmentally benign. Most particularly the present invention relates to an environmentally benign deicing
10 fluid composition which is obtained from various industrial waste streams or from the pure components.

BACKGROUND OF THE INVENTION

Freezing point lowering compositions are in widespread use for a variety of purposes, especially to
15 reduce the freezing point of an aqueous system so that ice cannot be formed or to melt formed ice. Generally, freezing point lowering compositions depend for their effectiveness upon the molar freezing point lowering effect, the number of ionic species which are made
20 available and the degree to which the composition can be dispersed in the liquid phase in which the formation of ice is to be precluded and/or ice is to be melted.

The most pervasive of the commonly used products for deicing are common salt, calcium chloride
25 and urea, with common salt (sodium chloride) being the least expensive and most commonly used. Common salt is widely used to melt ice on road surfaces and the like. In this manner the salt forms a solution with the

available liquid in contact with the ice and thereby forms a solution with a lower freezing point than the ice itself so that the ice is melted. Chloride salts however suffer from relatively severe drawbacks, such as the harmful effects on surrounding vegetation by preventing water absorption in the root systems, and its corrosive effects on animal skin such as the feet of animals, clothing, roadways and motor vehicles.

Other inorganic salts are also known to be useful as freezing point lowering agents such as magnesium chloride, potassium phosphates, sodium phosphates, ammonium phosphates, ammonium nitrates, alkaline earth nitrates, magnesium nitrate, ammonium sulfate, alkali sulfates.

Typical of solutions of low freezing points include brines, ethylene glycol and propylene glycol solutions. Brines are used to transfer heat at temperatures below the normal freezing point of water, and the ethylene glycol solutions are well known for use as coolants for automobiles and the like in regions in which the temperature may fall below the normal freezing point of water. Ethylene and propylene glycols are used in relatively large quantities at major airports in northern climates in order to keep air traffic flowing during inclement weather. The fluids are generally applied to the wings, fuselage and tail of aircraft as well as the runways to remove ice. However, these glycol compounds likewise have environmental drawbacks and can

be detrimental to sewage treatment processes.

Other prior art deicing fluids such as alcohols have toxic effects and high volatility particularly in the low molecular weight range and may be the cause of offensive smell and fire danger. Furthermore, mono- and polyhydric alcohols oxidize in the presence of atmospheric oxygen to form acids, which can increase corrosion of materials.

Due to the problems associated with deicing agents as described above there have been attempts to prepare even more deicing agents. For, example, Kaes, United States Patent No. 4,448,702 discloses the use of a freezing-point lowering composition and method which calls for the addition of a water soluble salt of at least one dicarboxylic acid having at least three carbon atoms, such as a sodium, potassium, ammonium or organoamine salt of adipic, glutaric, succinic or malonic acid.

Peel, United States Patent No. 4,746,449 teaches the preparation of a deicing agent comprising 12-75% acetate salts, trace-36% carbonate salts, 1-24% formate salts and 1-32% pseudolactate salts which is prepared from a pulp mill black liquor by fractionating the black liquor into a molecular weight fraction and concentrating the collected low molecular weight fraction to produce the deicing agent.

United States Patent No. 4,960,531, teaches that small amounts of methyl glucosides, i.e. less than

10%, can be employed as a trigger to conventional salt deicers.

However, all of these disclosures still require the presence of salts. Accordingly there still exists in the art a need for a deicing and/or anti-icing agent which is environmentally benign and relatively inexpensive to obtain.

SUMMARY OF THE INVENTION

Accordingly the present invention comprises a deicing and/or anti-icing agent which is environmentally benign and can be produced from relatively inexpensive feedstocks. In one embodiment of the present invention the deicing agent comprises a water soluble solution of hydroxycarboxylic acid based esters which are preferably prepared from waste process streams such as from the admixture of components of a pulp mill black liquor with distiller grain solubles and/or whey; the acid treatment of pre-distilled wood, agricultural and/or milk fermentation; the alcoholysis of distiller grain solubles or any combination thereof.

The compositions of the present invention can be applied to a wide variety of surfaces, particularly metallic and non-metallic surfaces of aircraft, which prevents icing, removes frozen water from the surface and prevents its reformation. The invention provides for a deicing composition which can be used on airplanes, runways, bridges, streets and the like. Further, the compositions can be used in heat transfer applications

and to applications in which it is vital to maintain a liquid in the unfrozen state, e.g., as in a fire extinguisher. Additionally, the present invention provides for an anti-icing composition which can be applied to a surface, such as bridges, prior to the onset of icing conditions in order to prevent icing from occurring.

The present invention further provides deicing and/or anti-icing agents which are prepared from the pure components, hydroxycarboxylic acid esters, hydrocarbyl aldoses, and or combinations thereof. In one further embodiment of the present invention there is provided a method for deicing and/or anti-icing a surface, the method comprising applying to the surface a composition comprising (a) a deicing and/or anti-icing agent comprising at least about 15 weight percent of a hydrocarbyl aldose and (b) water. In another further embodiment, there is provided a deicing and/or anti-icing agent composition comprising (a) a hydroxycarboxylic acid salt, (b) a hydrocarbyl aldose and (c) water.

DETAILED DESCRIPTION OF THE PRESENT INVENTION

The present invention provides a novel composition useful as a deicing agent and/or an anti-icing agent and a novel method of preparing the deicing and/or anti-icing agents.

The deicing agents of the present invention comprise a hydroxycarboxylic acid ester, a hydrocarbyl aldose, or both.

Hydroxycarboxylic acid esters are well known to those of ordinary skill in the art and typically comprise hydroxyformate, hydroxyacetate, hydroxypropionate, hydroxybutyrate, hydroxylaurate, hydroxypalmitate, hydroxyoleate, hydroxybenzoate as well as others. Preferred for use in the practice of the present invention are deicing agents comprising α -hydroxypropionate type esters such as alkyl lactates.

Hydrocarbyl aldoses are well known to those of ordinary skill in the art. Preferably the hydrocarbyl aldoses comprise alkyl aldoses and/or sorbitols.

The alkyl aldoses can be prepared by a continuous alcoholysis process for making mixed aldose from polysaccharides, and more particularly, for making mixed alkyl glycosides directly from starch, as described in United States Patent No. 4,223,129. A further process of producing aldoses for use in the practice of the present invention is described in United States Patent No. 4,329,449.

Typical of the alkyl aldoses useful in the practice of the present invention are alpha-methyl glucoside, beta-methyl glucoside, methyl furanosides, methyl maltosides, methyl maltotriosides, mixtures thereof and the like.

In addition to the hydroxycarboxylic acid esters and/or hydrocarbyl aldoses, a wide variety of other components may be included in the deicing and/or anti-icing compositions of the present invention. Along

with the free hydroxycarboxylic acid, preferably these include water soluble anionic hydroxycarboxylic acid salts. Generally these components may be added to the deicing and/or anti-icing compositions of the present invention or they are present in or are derived from the process waste streams from which the compositions of the present invention may be obtained.

Also, it is contemplated herein that anionic hydroxycarboxylic acid salts alone or with amino acids and/or water soluble salts of dicarboxylic acids having at least three carbon atoms, preferably selected from adipic, succinic, glutaric and malonic acids may also be included, but are not necessary to the practice of the present invention. These can be added separately such as through the addition of pulp mill black liquors or via alkali additions to hydroxycarboxylic acid containing compositions.

The deicing agents may be prepared from the pure chemical ingredients. For instance, a solution of 25% H₂O/10% sodium lactate/65% ethyl lactate was found to have no crystal formation at a temperature of -50°C.

However, it is contemplated by the present invention to obtain the deicing agents of the present invention from any of a number of industrial waste streams which comprise a water soluble solution of hydroxycarboxylic acid, since lactic acid as it occurs in dilute fermentation liquors is inexpensive. The purification of this material is difficult due to its

similarity in solubility characteristics to water as the presence of impurities such as dextrans, proteins and unfermented sugars. For instance, the present invention contemplates the use of waste stream selected from the group consisting of a grain stillage, a wood stillage, agricultural or milk fermentation and mixtures of any of the foregoing. Generally, the components of the present invention are present in or are derived by alcoholysis of the process waste streams. Typically these waste streams include components such as lactic acid fractions and low molecular weight sugars such as sorbitols, maltoses and glucoses.

By subjecting the waste streams to alcoholysis (with an alkyl alcohol) under conditions such as reacting with an alkyl alcohol in the presence of a cation exchange material or other acid, or the addition of an alkyl alcohol to a heated fermentation liquor as taught in Ind. Eng. Chem., 38, pg. 228, 1946 by E.M. Filachione and C.H. Fisher, at least some of the hydroxycarboxylic acids present are converted to the hydroxycarboxylic acid based esters and at least some of the sugars are converted to glucosides, thereby improving the overall acidity of the material. For instance, ethanol treatment of a typical agricultural fermentation waste stream comprising lactic acid and glucose would be partially converted to ethyl lactate and ethyl glucoside. The use of the alcoholysis process aids in increasing the concentration of the glycosides and hydroxycarboxylates,

thereby providing an improved product.

For example, components of the present invention can include, but are not limited to: ethyl lactate, glycerol, glycol lactate, ethyl glycinate, ethyl levulinate, ethylenecarbonate, glycerin carbonate, 5 pipecolic acid, tetrahydrofurfuryl acetate, tetrahydrofurfuryl tetrahydrofuroate, sorbitol, glucose glutamate, methyl glucosides, acetals and ketals of glycerol such as 2,2-dimethyl-1,3-dioxolane-4-methanol and salts thereof and the like. 10

As discussed above, although not critical for the present invention, the compositions of the present invention may further comprise high solubility salts in combination with the hydroxycarboxylates and glucosides. 15 For example, useful salts could include, but are not limited to: hydroxycarboxylic acid salts (including cesium, sodium, potassium, calcium and magnesium salts) such as sodium lactate; acetate salts such as cesium acetate, sodium acetate, potassium acetate; formate salts 20 such as sodium formate; citrate salts such as sodium citrate; amino acids and their salts such as lysine glutamate, sodium pyrrolidone carboxylate and sodium glucoheptonate; dicarboxylic acids salts such as sodium and potassium salts of adipic, glutaric, succinic and malonic acids; lignin components such as lignin 25 sulfonate; boric acid and its salts, glycerin and the like.

Glycols such as propylene glycol, ethylene

glycol may also be employed with the compositions of the present invention where desired.

5 The amount of the acid components, i.e. the hydroxycarboxylic acid esters, hydroxycarboxylic acid salts, lignins and glucosides, which are present in the compositions of the present invention may vary widely and still provide the improved freezing point lowering effect. Preferably, however, the compositions of the present invention comprise a total weight of acid
10 components ranging from about 10 to about 75 weight percent, more preferably from about 20 to about 75 weight percent and most preferably from about 30 to about 75 weight percent, based on the weight of acid and water combined.

15 The compositions of the present invention are considered non-toxic and readily breakdown, even at low temperatures, in the natural environment without any significant adverse effects. Moreover, the compositions of the present invention are considered to have lower
20 Biological Oxygen Demand (BOD) requirements than comparable de-icers, and a lesser amount of the composition of the present invention (higher water concentration) is required to prevent ice formation at a particular ambient air temperature or quantity of ice.
25 Since the concentration of an anti-icer that is applied should be sufficient to prevent significant ice formation under reasonable conditions much smaller material usage for the composition of the present invention at

particular outside air temperatures and precipitate rates results.

5 In the methods of the present invention, the deicing and/or anti-icing compositions of the present invention are combined with water and applied, such as by spraying, onto the surface desired to be treated. In the case of deicing, the surface already has ice formed thereon, and the deicing compositions of the present invention melt the ice already formed and are further effective in preventing additional ice formation. In the case of anti-icing, upon learning of a weather forecast which predicts possible dangerous icing conditions, the roads and bridges or other surfaces can be pretreated with the anti-icing compositions of the present invention in order to prevent ice formation on the surfaces.

15 In one embodiment of a method of the present invention where the deicing and/or anti-icing agent includes a hydrocarbyl aldohydrate without a hydroxycarboxylic acid ester component, the amount of hydrocarbyl aldohydrate employed to obtain the benefits of the present invention is at least about 15 weight percent based on the weight of the deicing and/or anti-icing agent (not including water) and can comprise up to 100 weight percent. Typically, however the amount of hydrocarbyl aldohydrate is from about 15 to about 90 weight percent, such as from about 30 to about 90 weight percent, and more particularly from about 50 to about 75 weight percent.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following examples are provided for illustrative purposes and are not to be construed to limit the scope of the claims in any manner whatsoever.

5 Unless otherwise indicated, melting points were determined using a Differential Scanning Calorimeter (DSC). Scans were conducted from -160°C up to 30°C at 10°C per minute on a 1 mg sample taken from a 20 g mixture. The complete melt point was utilized.

10

EXAMPLE 1

A mixture of 25% by weight water, 65% by weight ethyl lactate and 10% by weight sodium lactate was prepared. No crystal formation was observed at a temperature of -50°C.

15

EXAMPLE 2

A mixture of 50% by weight water and 50% by weight ethyl lactate was prepared. The mixture had a melting point of -18°C.

20

EXAMPLE 3

A mixture of 70% by weight water, 24% by weight ethyl lactate and 6% by weight sodium lactate was prepared. The mixture had a melting point of -25°C as determined by DSC and a pH of 6.0. For comparison, a 70% by weight water/30% by weight ethylene glycol solution
25 has a melting point of -18°C.

EXAMPLE 4

The addition of 50% by weight of a 50% mixture of ethyl lactate in water to a concentrated, filtered

corn steep liquor (containing 50% water and 50% solids comprising mostly lactic acid and sugars) caused a reduction in freezing point from -11°C to -16°C . The addition of 2% by weight sodium lactate further reduced the freezing point to -20°C .

EXAMPLE 5

A mixture of 60% by weight water, 20% by weight sodium lactate, 2% by weight proline (an amino acid), 8% by weight sorbitol and 10% by weight sodium pyrrolidone carboxylate (sodium PCA) was prepared. No crystal formation at -35°C was observed. The pH was 6.57. For comparison a 50% by weight solution propylene glycol has a freezing point of -36°C .

EXAMPLE 6

A mixture of 12% by weight methyl lactate, 44% by weight methyl glucoside and 44% by weight water was prepared. A melting point of -18°C was observed. The mixture had a pH of 5.

EXAMPLE 7

A mixture containing 35% by weight methyl lactate, 35% by weight methyl glucoside and 30% by weight water has a melting point of -21°C as determined by DSC.

EXAMPLE 8

A filtered concentrated liquid residue of a 50% mixture of corn stillage and steepwater containing 50% by weight water with a freezing point of -12°C is heated to 90°C and treated with 5% ethanol for 8 hours. The resulting mixture has a freezing point of -17°C . The

addition of 2% sodium lactate further reduces the freezing point to -21°C.

The above-referenced patents and publications are hereby incorporated by reference.

5 Many variations of the present invention will suggest themselves to those skilled in the art in light of the above-detailed description. For example, any process stream which contains components from which hydroxycarboxylates can be prepared may be used to
10 prepare the compositions of the present invention. Additionally, a wide variety of lignins, sugars and glucosides may be present in the compositions of the present invention. All such obvious modifications are within the full intended scope of the appended claims.

CLAIMS

1. A method of preparing a substantially environmentally benign deicing composition, said method comprising:

5 (a) recovering an industrial waste stream comprising a hydroxycarboxylic acid; and

(b) alcoholizing at least a portion of hydroxycarboxylic acids in said recovered waste stream with an alkyl alcohol to convert said portion of hydroxycarboxylic acids to water soluble hydroxycarboxylic acid esters.

2. A deicing composition comprising a water soluble hydroxycarboxylic acid ester.

3. A deicing composition as defined in Claim 2 wherein said hydroxycarboxylic acid ester is selected from the group consisting of hydroxyformate, hydroxyacetate, hydroxypropionate, hydroxybutyrate, hydroxylaurate, hydroxypalmitate, hydroxyoleate, hydroxybenzoate, and mixtures thereof.

4. A deicing composition as defined in Claim 3 wherein said hydroxycarboxylic acid ester comprises an alkyl lactate.

5. A deicing composition as defined in Claim 2 further comprising a low molecular weight glycosides.

25 6. A deicing composition as defined in Claim 2 further comprising a lignin compound.

7. A deicing composition as defined in Claim 2 further comprising an anionic hydroxycarboxylic acid

salts alone or with amino acids.

8. A deicing composition as defined in Claim 2 further comprising water soluble salts of dicarboxylic acids having at least three carbon atoms.

5 9. A deicing composition as defined in Claim 8 wherein said dicarboxylic acid is selected from the group consisting of adipic acid, succinic acid, glutaric acid, malonic acid and mixtures thereof.

10 10. A deicing composition as defined in Claim 2 wherein said hydroxycarboxylic acid ester is selected from the group consisting of ethyl lactate, glycol lactate, methyl lactate, ethyl glycinate, ethyl levulinate, ethylenecarbonate, glycerin carbonate, pipecolate, tetrahydrofurfuryl acetate,
15 tetrahydrofurfuryl tetrahydrofuroate, glucose glutamate, and mixtures thereof.

11. A deicing composition as defined in Claim 2 further comprising a salt selected from the group consisting of sodium lactate, cesium acetate, sodium
20 acetate, potassium acetate, sodium formate, sodium citrate, lysine glutamate, sodium glucoheptonate, sodium and potassium salts of adipic, glutaric, succinic and malonic acids, lignin sulfonate and mixtures thereof.

12. A deicing composition as defined in Claim
25 2 wherein said hydroxycarboxylic acid ester is obtained by alcoholizing hydroxycarboxylic acids contained in industrial waste streams, said waste streams comprising distiller grain solubles, whey, pulp mill black liquor,

furfuryl derivatives from oats or mixtures thereof, with an alkyl alcohol.

13. A deicing composition as defined in Claim 2 which is obtained by internal alcoholysis resulting from the acid treatment of pre-distilled wood, agricultural fermentation and/or milk fermentation.

14. A method as defined in Claim 1 wherein said waste stream further comprises sugars and said alcoholizing step further comprises converting at least a portion of said sugars to glycosides.

15. A method as defined in Claim 1 wherein said sugars are selected from the group consisting of sorbitols, maltoses, glucoses and mixtures thereof.

16. A method of preparing a substantially benign deicing composition, said method comprising:

(a) recovering an industrial waste stream comprising a water soluble hydroxycarboxylic acid; and

(b) adding an effective amount of a freezing point lowering compound to said industrial waste stream, said freezing point lowering compound selected from the group consisting of water soluble hydroxycarboxylic acid esters, glycosides and mixtures thereof.

17. A method of preparing a substantially environmentally benign deicing composition, said method comprising:

(a) recovering an industrial waste stream comprising a sugar compound; and

(b) alcoholizing at least a portion of the

sugar compound in said recovered waste stream with an alkyl alcohol to convert said portion of sugar compound to alkyl glucosides.

18. A method as defined in Claim 17 wherein
5 said sugar comprises glucose, said alkyl alcohol comprises ethanol and said alkyl glucoside comprises ethyl glucoside.

19. A method of preparing a substantially environmentally benign deicing composition, said method
10 comprising:

(a) recovering an industrial waste stream comprising a water soluble hydroxycarboxylic acid; and

(b) reacting at least a portion of said water soluble hydroxycarboxylic acid to form anionic
15 hydroxycarboxylic acid salts.

20. A method for deicing and/or anti-icing a surface, said method comprising:

applying to said surface a composition comprising:

(a) a deicing and/or anti-icing agent
20 comprising at least about 15 weight percent of a hydrocarbyl aldose and

(b) water.

21. A method as defined in Claim 20 wherein
25 said hydrocarbyl aldose comprises an alkyl aldose.

22. A method as defined in Claim 20 wherein said hydrocarbyl aldose is selected from the group consisting of glucosides, furanosides, maltosides,

maltotriosides, glucopyranosides and mixtures of any of the foregoing.

23. A method as defined in Claim 21 wherein said alkyl aldose comprises alpha-methyl glucoside.

5 24. A method as defined in Claim 20 wherein said hydrocarbyl aldose comprises sorbitol.

25. A method as defined in Claim 20 wherein said deicing and/or anti-icing composition further comprises a freezing point lowering additive selected from the group consisting of hydroxycarboxylic acid salts, acetate salts, formate salts, citrate salts, amino acid and their salts, dicarboxylic acid salts, lignin components, boric acid at its salts and mixtures thereof.

10

26. A method as defined in Claim 24 wherein said freezing point lowering additive is selected from the group consisting of sodium lactate, cesium acetate, sodium acetate, potassium acetate, sodium formate, sodium citrate, lysine glutamate, sodium glucoheptonate, sodium and potassium salts of adipic, glutaric, succinic and malonic acids, boric acid, sodium borate, lignin sulfonate and mixtures thereof.

15

20

27. A de-icing and/or anti-icing agent composition comprising:

- 25 (a) a hydroxycarboxylic acid salt,
 (b) a hydrocarbyl aldose and
 (c) water.

28. A composition as defined in Claim 27 wherein said hydroxycarboxylic acid salt comprises sodium

lactate.

29. A composition as defined in Claim 27 wherein said hydrocarbyl aldose comprises an alkyl aldose.

5 30. A composition as defined in Claim 27 wherein said hydrocarbyl aldose is selected from the group consisting of glucosides, furanosides, maltosides, maltotriosides, glucopyranosides and mixtures of any of the foregoing.

10 31. A method as defined in Claim 29 wherein said alkyl aldose comprises alpha-methyl glucoside.

32. A method as defined in Claim 27 wherein said hydrocarbyl aldose comprises sorbitol.

15 33. A composition as defined in Claim 27 further comprising a freezing point lowering additive selected from the group consisting of cesium acetate, sodium acetate, potassium acetate, sodium formate, sodium citrate, lysine glutamate, sodium glucoheptonate, sodium and potassium salts of adipic, glutaric, succinic and
20 malonic acids, boric acid, sodium borate lignin sulfonate and mixtures thereof.

34. A de-icing and/or anti-icing agent composition comprising:

- 25 (a) a hydrocarbyl aldose,
(b) a hydroxycarboxylic acid ester, and
(c) water.

INTERNATIONAL SEARCH REPORT

International application No.

PCT/US98/20300

A. CLASSIFICATION OF SUBJECT MATTER

IPC(6) : C09K 3/18, 3/00

US CL : 252/70; 106/13

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 252/70; 106/13

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category*	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4,746,449 A (PEEL) 24 MAY 1988, see examples and claims.	1-2,13,19
Y		----- 1-2,13,19
Y,P	US 5,718,834 A (POLLMANN et al) 17 FEBRUARY 1998, Col. 4, lines 23-46.	2-4,7-13,19



Further documents are listed in the continuation of Box C.



See patent family annex.

* Special categories of cited documents:	*T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
A document defining the general state of the art which is not considered to be of particular relevance	*X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
B earlier document published on or after the international filing date	*Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art
L document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)	*Z* document member of the same patent family
O document referring to an oral disclosure, use, exhibition or other means	
P document published prior to the international filing date but later than the priority date claimed	

Date of the actual completion of the international search

09 DECEMBER 1998

Date of mailing of the international search report

20 JAN 1999

Name and mailing address of the ISA/US
Commissioner of Patents and Trademarks
Box PCT
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer:

ANTHONY J. GREEN

Telephone No. (703)-308-0661